

FLEXI Outdoor

Classic - Outdoor Kiosk



Technical data

Structure

Powder-coated aluminium profiles

Monitor

Litemax, 1600 Nits
19" / 22"

Touchscreen

Zytronic anti-glare glass
Projected capacitive touch

Controller

Automatic temperature management
Emergency shutdown/startup
Unit surveillance
Noise-cancelling fan system

Protection & Resistance

IP65 rating
Triple-layer sealing
Removable dust filter
Standard heating unit 450W
4 ventilation fans
-20 to 40 degrees Celcius

Security

Double-point locking system

Mounting

Concrete foundation

Access

Front opening

Rec. max pc size

Width: 200mm
Height: 300mm
Depth: 100mm

Weight

Approximately 85 kg

Footstand

Powder-coated aluminium



Options

Branding

Graphic laminate
Special RAL colors

Hardware

Payment interface
Card reader
Scanner QR - 2D - 1D
RFID scanner
Receipt printer
A4 printer
Intercom VOIP
Speakers
Camera
Keyboard
LED lighting
Antenna

Conditional Resistance

Aircondition unit
(Above 40 degrees Celcius)
Heating unit 850W
(Below -20 degrees Celcius)

Access

Rear opening

ROSENDAHL CONCEPTKIOSK A/S

+45 76 72 02 60

info@conceptkiosk.com

www.conceptkiosk.com

Thorsvej 233 • 7200 Grindsted • Denmark

facebook.com/conceptkiosk

linkedin.com/company/conceptkiosk