

# FLEXI Outdoor Wall

## Newline - Outdoor Kiosk



### Technical data

#### Structure

Powder-coated aluminium profiles

#### Monitor

LiteMAX, 1600 nits  
19" / 22"

#### Touchscreen

Zytronic anti-glare touch glass  
Projected capacitive touch

#### Controller

Auto temperature management  
Emergency stop/start  
Unit surveillance  
Noise-cancelling fan system

#### Protection & Resistance

IP65 rating  
Triple-layer sealing  
Removable dust filter  
Standard heating unit 450W  
High output ventilation system  
-20 to 40 degrees Celcius

#### Security

Triple-point locking system

#### Mounting

Wall-hanging

#### Access

Front opening

#### Rec. max pc size

Width: 200mm  
Height: 300mm  
Depth: 100mm

#### Weight

Approximately 85 kg



### Options

#### Branding

Graphic laminate  
Special RAL colors

#### Hardware

Payment interface  
Card reader  
Scanner QR - 2D - 1D  
RFID scanner  
Receipt printer  
A4 printer  
Intercom VOIP  
Speakers  
Camera  
Keyboard  
LED lighting  
Antenna

#### Conditional resistance

Aircondition unit  
(Above 40 degrees Celcius)  
Heating unit 850W  
(Below -20 degrees Celcius)

ROSENDAHL CONCEPTKIOSK A/S

+45 76 72 02 60

info@conceptkiosk.com

www.conceptkiosk.com

Thorsvej 233 • 7200 Grindsted • Denmark

facebook.com/conceptkiosk

linkedin.com/company/conceptkiosk